NSN 4320-01-413-8867

Reciprocating Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-413-8867

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Cylinder Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Unthreaded external
Discharge Connection Quantity:
1
Discharge Connection Type:
Unthreaded external
Current Type:
Dc
Media For Which Designed:
Water, fresh
Pump Quantity:
1
Pumping Element Type:
Diaphragm
Cooling Method:
Water-air cooled
vvater-air cooled
Maximum Discharge Flow Rate:
Maximum Discharge Flow Rate:
Maximum Discharge Flow Rate: 2.5 gallons per minute
Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift:
Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet
Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position:
Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position: Horizontal
Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position: Horizontal Pump Reciprocating Design:
Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position: Horizontal Pump Reciprocating Design: Single acting
Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position: Horizontal Pump Reciprocating Design: Single acting Reciprocating Stroke Type:
Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position: Horizontal Pump Reciprocating Design: Single acting Reciprocating Stroke Type: Fixed
Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position: Horizontal Pump Reciprocating Design: Single acting Reciprocating Stroke Type: Fixed Operation Relationship Design:
Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position: Horizontal Pump Reciprocating Design: Single acting Reciprocating Stroke Type: Fixed Operation Relationship Design: Simultaneous

Partially enclosed

NSN 4320-01-413-8867

Reciprocating Pump Unit - Page 2 of 2



Current Rating In Amps:
1.8
Prime Mover Power Rating:
43.2 watts
Voltage In Volts:
24.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400