## NSN 4320-01-413-8867

Reciprocating Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-413-8867

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Cylinder Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Unthreaded external
Discharge Connection Quantity:
1
Discharge Connection Type:
Unthreaded external
Current Type:
Dc
Media For Which Designed:
Water, fresh
Pump Quantity:
1
Pumping Element Type:
Pumping Element Type: Diaphragm
Diaphragm
Diaphragm  Cooling Method:
Diaphragm  Cooling Method:  Water-air cooled
Diaphragm  Cooling Method:  Water-air cooled  Maximum Discharge Flow Rate:
Diaphragm  Cooling Method:  Water-air cooled  Maximum Discharge Flow Rate:  2.5 gallons per minute
Diaphragm  Cooling Method:  Water-air cooled  Maximum Discharge Flow Rate:  2.5 gallons per minute  Suction Lift:
Diaphragm  Cooling Method:  Water-air cooled  Maximum Discharge Flow Rate:  2.5 gallons per minute  Suction Lift:  4.0000 feet
Diaphragm  Cooling Method: Water-air cooled  Maximum Discharge Flow Rate: 2.5 gallons per minute  Suction Lift: 4.0000 feet  Pumping Element Operating Position:
Diaphragm  Cooling Method: Water-air cooled  Maximum Discharge Flow Rate: 2.5 gallons per minute  Suction Lift: 4.0000 feet  Pumping Element Operating Position: Horizontal
Diaphragm  Cooling Method: Water-air cooled  Maximum Discharge Flow Rate: 2.5 gallons per minute  Suction Lift: 4.0000 feet  Pumping Element Operating Position: Horizontal  Pump Reciprocating Design:
Diaphragm  Cooling Method: Water-air cooled  Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet  Pumping Element Operating Position: Horizontal  Pump Reciprocating Design: Single acting
Diaphragm  Cooling Method: Water-air cooled  Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet  Pumping Element Operating Position: Horizontal  Pump Reciprocating Design: Single acting  Reciprocating Stroke Type:
Diaphragm Cooling Method: Water-air cooled Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position: Horizontal Pump Reciprocating Design: Single acting Reciprocating Stroke Type: Fixed
Cooling Method: Water-air cooled Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position: Horizontal Pump Reciprocating Design: Single acting Reciprocating Stroke Type: Fixed Operation Relationship Design:
Diaphragm Cooling Method: Water-air cooled Maximum Discharge Flow Rate: 2.5 gallons per minute Suction Lift: 4.0000 feet Pumping Element Operating Position: Horizontal Pump Reciprocating Design: Single acting Reciprocating Stroke Type: Fixed Operation Relationship Design: Simultaneous

Partially enclosed

## NSN 4320-01-413-8867

Reciprocating Pump Unit - Page 2 of 2



<b>Current Rating In Amps:</b>
1.8
Prime Mover Power Rating:
43.2 watts
Voltage In Volts:
24.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A19400