

View Online at <https://aerobasegroup.com/nsn/4320-01-416-5973>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

3

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Environmental Protection:

Explosion proof

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Navy weapon system ja nimitz class cvn

Maximum Discharge Flow Rate:

300.0 gallons per minute

Discharge Pressure:

200.0 pounds per square inch gage

Total Head:

170.0000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

12.97 and 6.48

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

2.000-11 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

3.0 horsepower

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A19400