

View Online at <https://aerobasegroup.com/nsn/4320-01-418-7111>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**End Application:**

Weapons system kk, 170' patrol coastal (pc-1) class ships

**Maximum Discharge Flow Rate:**

110.0 gallons per minute

**Discharge Pressure:**

45.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

520.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Rotary Pump Design:**

Vane

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

7.3

**Prime Mover Power Rating:**

7.5 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Fuel transfer pump; suction lift is 10in. Hg

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400