

View Online at <https://aerobasegroup.com/nsn/4320-01-419-6341>

Prime Mover Quantity:

1

Mounting Type:

Frame

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Power Drive Operating Pressure:

40.0 pounds per square inch gage

Pump Quantity:

1

Pumping Element Type:

Piston

Discharge Pressure:

400.0 pounds per square inch gage

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Fixed

Prime Mover Type:

Pneumatic motor

Discharge Connection Thread Size And Series/type Designator:

0.500-14 npt

Intake Connection Thread Size And Series/type Designator:

0.500-14 npt

Special Features:

7Includes a haskel air driven transfer pump with electric stroke counter model p/n 17860-2-58896; a 0-400psi outlet pressure gauge, roll bar frame assembly; 3/8in. Npt ball selector valve, 30in. Vacuum gauge; two 3/8in. Npt angle check valves; speed control valve; a 0-160psi air drive inlet gauge, an air filter, an air regulator, two 1/2in. Npt ball shut-off valves, a relief valve set at 300psi, and the required pipe fittings; has a 1/2in. Npt air drive inlet port, 40-150psi air drive inlet pressure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400