

View Online at <https://aerobasegroup.com/nsn/4320-01-421-5162>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Environmental Protection:

Explosion proof

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

150.0 gallons per minute

Total Head:

150.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.07 and 1.87 and 0.93

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Prime Mover Power Rating:

0.750 horsepower

Voltage In Volts:

208.0 and 230.0 and 460.0

Phase:

Three

Special Features:

Carbon steel and stainless steel construction; viton seals; drain plug; fill and vent; 212.0deg f.Max temp; 4-7/16in.Dia impeller

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400