

View Online at <https://aerobasegroup.com/nsn/4320-01-422-5733>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

35.0 gallons per minute

**Discharge Pressure:**

80.2 pounds per square inch gage

**Total Head:**

185.000 feet

**Operating Speed At Rated Capacity:**

3550.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

12.7

**Prime Mover Power Rating:**

7.5 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

1.500 in. Suction, 1.000 in. Discharge connections; ductile iron housing; close coupled

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400