

View Online at <https://aerobasegroup.com/nsn/4320-01-423-3431>

**Prime Mover Quantity:**

1

**Mounting Type:**

Frame

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Sewage

**Pump Quantity:**

1

**End Application:**

Strategic sealift conversion ships class

**Maximum Discharge Flow Rate:**

100.0 gallons per minute

**Discharge Pressure:**

58.5 pounds per square inch gage

**Total Head:**

135.000 feet

**Suction Lift:**

16.000 feet

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Current Rating In Amps:**

17.2

**Prime Mover Power Rating:**

15.0 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400