

View Online at <https://aerobasegroup.com/nsn/4320-01-423-4431>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Frame

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Splash proof

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Strategic sealift conversion ships class

Maximum Discharge Flow Rate:

160.0 gallons per minute

Discharge Pressure:

80.2 pounds per square inch gage

Total Head:

185.000 feet

Suction Lift:

30.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Double

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

25.2

Prime Mover Power Rating:

20.0 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

2.000 in.Discharge, 2.500 in.Intake connections

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400