NSN 4320-01-423-7714

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-423-7714

Spline Minor Diameter:
0.797 inches
Spline Major Diameter:
0.994 inches
Mounting Type:
Flange
Spline Quantity:
6
Mounting Hole Diameter:
0.515 inches
Mounting Hole Quantity:
2
Bolt Hole Quantity:
4
Operating Speed At Rated Capacity In Rpm:
510.0
Mounting Bolt Circle Diameter:
4.187 inches
End Application:
Ticonderoga class cg (47)
Drive Shaft Type:
Splined, straight external
Housing Material:
Steel
Shaft Rotation Direction:
Clockwise
Shaft Protrusion Length:
1.746 inches
Connection Quantity:
1 and 1
Connection Type:
Inlet and outlet
Connection Design:
Flanged
Bolt Hole Thread Size:
0.312-18
Spline Length:
1.000 inches
Displacement Type:
Constant
Constant Displacement Per Revolution:
4.600 cubic inches

NSN 4320-01-423-7714

Hydraulic Motor - Page 2 of 2



Connection Government Specification/std:

Single manifold mount per white hydraulics, inc.

Bolt Hole Spacing:

1.120 in. By 2.500 in.

Special Features:

Reversable by switching ports

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T103-f