NSN 4320-01-424-1664

Rotary Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-424-1664

| Discharge Connection Quantity: |
|--|
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Drive Connection Type: |
| Gear |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| End Application: |
| Tf33p100 |
| Discharge Pressure: |
| 20.0 pounds per square inch gage |
| Operating Speed At Rated Capacity: |
| 4070.0 revolutions per minute |
| Pump Rotation Direction: |
| Counterclockwise |
| Rotary Pump Design: |
| Gear |
| Operation Method: |
| Powered |
| Drive Shaft Type: |
| Splined, straight external |
| Drive Shaft End Diameter: |
| 0.650 inches |
| Drive Shaft Length: |
| 1.181 inches |
| Discharge Connection Thread Size And Series/type Designator: |
| 0.875-14 unf |
| Product Name: |
| Scavenge pump |
| Special Features: |
| T.O. 2j-tf33-44 fig 26 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A19400 |