

View Online at <https://aerobasegroup.com/nsn/4320-01-426-7695>

Prime Mover Quantity:

1

Cylinder Quantity:

1

Intake Connection Quantity:

2

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

2

Discharge Connection Type:

Threaded internal

Media For Which Designed:

Hydrocarbon fuels and oils or water, fresh

Power Drive Operating Pressure:

100.0 pounds per square inch gage

Pump Quantity:

1

Pumping Element Type:

Piston

End Application:

Engine, aircraft, f100-pw-10 (f-15a/b/c/d)

Maximum Discharge Flow Rate:

1.3 gallons per minute

Discharge Pressure:

750.0 pounds per square inch gage

Total Head:

1730.250 feet

Pumping Element Operating Position:

Vertical

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Fixed

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Pneumatic motor

Discharge Connection Thread Size And Series/type Designator:

0.500-14 npt

Intake Connection Thread Size And Series/type Designator:

0.500-14 npt and 0.750-14 npt

Prime Mover Power Rating:

0.75 horsepower

Special Features:

Used on 4920-01-388-4387 test stand, electrical, hydraulic; 1/2npt inlet/outlet air connections; 1/2-3/4npt liquid outlet/inlet connections; exhaust muffler on air outlet port

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400