

View Online at <https://aerobasegroup.com/nsn/4320-01-426-7870>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Flange

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Navy weapons systems jm, emory s. Land class as

Maximum Discharge Flow Rate:

24.0 gallons per minute

Total Head:

14.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Double

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

0.23 and 0.47

Discharge Connection Thread Size And Series/type Designator:

0.500-14 npt

Prime Mover Power Rating:

0.25 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Double intake; motor frame totally enclosed non-ventilated

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400