## NSN 4320-01-426-7870

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-426-7870

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Flange
Stage Quantity:
1
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Media For Which Designed:
Water, fresh
Pump Quantity:
1
Cooling Method:
Air to air cooled
End Application:
Navy weapons systems jm, emory s. Land class as
Maximum Discharge Flow Rate:
24.0 gallons per minute
Total Head:
14.000 feet
Operating Speed At Rated Capacity:
3450.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Double
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:

0.23 and 0.47

## NSN 4320-01-426-7870

Centrifugal Pump Unit - Page 2 of 2

**Fiig:** A19400



Discharge Connection Thread Size And Series/type Designator:
0.500-14 npt
Prime Mover Power Rating:
0.25 horsepower
Voltage In Volts:
230.0 and 460.0
Phase:
Three
Special Features:
Double intake; motor frame totally enclosed non-ventilated
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No