NSN 4320-01-429-1284

Reciprocating Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-429-1284 **Mounting Type:** Base **Cylinder Quantity: Intake Connection Quantity: Intake Connection Type:** Threaded internal **Discharge Connection Quantity: Discharge Connection Type:** Threaded external and threaded internal Media For Which Designed: Hydrocarbon fuels and oils **Pumping Element Type:** Diaphragm **End Application:** Onboard 400 ft wagb coast guard vessels **Maximum Discharge Flow Rate:** 42.0 gallons per minute **Discharge Pressure:** 125.0 pounds per square inch gage **Total Head:** 289.000 feet **Operating Speed At Rated Capacity:** 466.7 strokes per minute **Pumping Element Operating Position:** Horizontal **Pump Reciprocating Design:** Double acting **Reciprocating Stroke Type: Volume Control Type:** Pressure compensation **Control Location:** Center **Operation Method:** Powered

Discharge Connection Thread Size And Series/type Designator:

0.750-14 npt and 1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

0.500-14 npt and 1.000-11-1/2 npt

NSN 4320-01-429-1284

Reciprocating Pump - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400