

View Online at <https://aerobasegroup.com/nsn/4320-01-429-5341>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Frame

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, salt

**Pump Quantity:**

1

**End Application:**

Navy weapon system code th, strategic sealift conversion ships class

**Maximum Discharge Flow Rate:**

350.0 gallons per minute

**Total Head:**

125.000 feet

**Operating Speed At Rated Capacity:**

1800.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Prime Mover Power Rating:**

20.0 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Pre-cooling pump; casing: cast duct iron, impeller: ni-al-brz astm b148 alooy 9d, shaft and sleeve: st stl aisi 316

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400