

View Online at <https://aerobasegroup.com/nsn/4320-01-432-1478>

**Mounting Type:**

Flange

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Rectangular flange

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Rectangular flange

**Drive Connection Type:**

Close coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils and liquid

**End Application:**

Navy weapon system code ar, shipboard material handling equipment (mhe); scaper-tract

**Maximum Discharge Flow Rate:**

26.0 gallons per minute

**Discharge Pressure:**

100.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1200.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Counterclockwise

**Rotary Pump Design:**

Vane

**Operation Method:**

Powered

**Special Features:**

Inlet 2.50in.Dia; outlets 1.00in.Dia and 0.75in.Dia; maybe used w/ synthetic fire resisant fluids (phosphate esters, fluorocarbon and silicone elastomers)s

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400