

View Online at <https://aerobasegroup.com/nsn/4320-01-432-2505>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Frame

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh or water, salt

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Navy weapon system code th, strategic sealift conversion ships class; forward and aft fire pump

Maximum Discharge Flow Rate:

1115.0 gallons per minute

Total Head:

336.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

150.0 horsepower

Voltage In Volts:

460.0

Phase:

Three

Special Features:

6.0in suction 150lb. Ansi flg; 4.0in.Discharge 150lb ansi flg;

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400