

View Online at <https://aerobasegroup.com/nsn/4320-01-432-3008>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Splash proof

Pump Quantity:

1

Cooling Method:

Blower cooled

End Application:

Navy weapons systems jk, wasp class lhd

Maximum Discharge Flow Rate:

16.0 gallons per minute

Discharge Pressure:

100.0 pounds per square inch gage

Total Head:

30.000 feet

Suction Lift:

4.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

0.94 and 0.47

Prime Mover Power Rating:

0.5 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

3/4in. Suction, 3/4in. Discharge; 316 stainless steel

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400