NSN 4320-01-433-2574

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-433-2574 **Thread Direction:** Right-hand **Torque Load Rating:** 2915.0 inch-pounds or 3401.0 inch-pounds **Spline Major Diameter:** 0.875 inches **Mounting Type:** Flange **Spline Quantity:** 13 **Mounting Hole Diameter:** 0.560 inches **Mounting Hole Quantity: Thread Size:** A0.875-14 **Operating Speed At Rated Capacity In Rpm:** 651.0 **Mounting Bolt Circle Diameter:** 5.740 inches **End Application:** Navy weapons systems jl, tarawa class lha Pitch Diameter: 0.758 inches **Drive Shaft Type:** Splined, involute external **Screw Thread Series Designator:** Unf **Shaft Rotation Direction:** Clockwise and counterclockwise **Thread Location:** Internal **Shaft Protrusion Length:** 1.590 inches Spline Pitch: 16/32 **Connection Quantity:**

2 **Connection Type:** Inlet and outlet **Connection Design:** Threaded

NSN 4320-01-433-2574 Hydraulic Motor - Page 2 of 2



| Spline Length: |
|--|
| 1.000 inches |
| Displacement Type: |
| Variable |
| Constant Displacement Per Revolution: |
| 7.100 cubic inches |
| Mounting Bolt Hole Spacing: |
| 5.740 |
| Special Features: |
| Sae"b" 2-bolt mounting flange; 0.830 in. Od 13 teeth splined through shaft with brake mount; sae o-ring ports; 7/16-20 unf sae o-ring vent |
| plug 25deg off center |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T103-f |
| |