## NSN 4320-01-433-2574

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-433-2574 **Thread Direction:** Right-hand **Torque Load Rating:** 2915.0 inch-pounds or 3401.0 inch-pounds **Spline Major Diameter:** 0.875 inches **Mounting Type:** Flange **Spline Quantity:** 13 **Mounting Hole Diameter:** 0.560 inches **Mounting Hole Quantity: Thread Size:** A0.875-14 **Operating Speed At Rated Capacity In Rpm:** 651.0 **Mounting Bolt Circle Diameter:** 5.740 inches **End Application:** Navy weapons systems jl, tarawa class lha Pitch Diameter: 0.758 inches **Drive Shaft Type:** Splined, involute external **Screw Thread Series Designator:** Unf **Shaft Rotation Direction:** Clockwise and counterclockwise **Thread Location:** Internal **Shaft Protrusion Length:** 1.590 inches Spline Pitch: 16/32 **Connection Quantity:** 

2 **Connection Type:** Inlet and outlet **Connection Design:** Threaded

## **NSN 4320-01-433-2574** Hydraulic Motor - Page 2 of 2



Spline Length:
1.000 inches
Displacement Type:
Variable
Constant Displacement Per Revolution:
7.100 cubic inches
Mounting Bolt Hole Spacing:
5.740
Special Features:
Sae"b" 2-bolt mounting flange; 0.830 in. Od 13 teeth splined through shaft with brake mount; sae o-ring ports; 7/16-20 unf sae o-ring vent
plug 25deg off center
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T103-f