

View Online at <https://aerobasegroup.com/nsn/4320-01-436-7259>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Liquid

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Mars clas afs

Discharge Pressure:

75.0 pounds per square inch gage

Suction Lift:

10.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Prime Mover Power Rating:

0.50 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400