

View Online at <https://aerobasegroup.com/nsn/4320-01-440-7388>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Hand truck

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils or water, salt

Pump Quantity:

1

Pumping Element Type:

Diaphragm

Cooling Method:

Air to air cooled

End Application:

Depmeds

Maximum Discharge Flow Rate:

43.3 gallons per minute

Discharge Pressure:

6.5 pounds per square inch gage

Total Head:

30.000 feet

Suction Lift:

15.000 feet

Operating Speed At Rated Capacity:

60.0 strokes per minute

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Fixed

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

4.9

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Prime Mover Power Rating:

0.750 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Cable 480 in.Lg from face of plug to strain relief

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by motor guard, elec cable 120v plug installed and spares and hardware kits

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400