

View Online at <https://aerobasegroup.com/nsn/4320-01-443-9476>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Quick disconnect

Discharge Connection Quantity:

1

Discharge Connection Type:

Quick disconnect

Media For Which Designed:

Water, fresh

Pump Quantity:

1

End Application:

Navy weapons code th, strategic sealift conversion ships class

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

0.5 horsepower

Special Features:

De-ionized water fill pump assembly; includes a 2pst toggle switch on motor, a check valve, a filter, a 0.50in. Diameter polyurethane suction hose, a 0.375in. Diameter polyurethane pressure and purge hoses and fittings; pump unit is mounted on a 0.1875in. Thick aluminum plate on four rubber standoffs inside a polypropylene plastic box with a hinged lid; has flexible viton impeller

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400