

View Online at <https://aerobasegroup.com/nsn/4320-01-444-1176>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Hydrocarbon fuels and oils

Pump Quantity:

1

End Application:

Navy weapons code ar, shipboard material handling equipment (mhe)

Maximum Discharge Flow Rate:

2.25 gallons per minute and 0.60 gallons per minute

Discharge Pressure:

250.0 pounds per square inch gage and 3000.0 pounds per square inch gage

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

90.0 and 240.0

Discharge Connection Thread Size And Series/type Designator:

0.5625-18 unf

Intake Connection Thread Size And Series/type Designator:

0.750-16 unf

Voltage In Volts:

12.0

Special Features:

Includes check valve and adjustable relief valve; has two 3/8-16 unc mounting holes in base, a no. 10-32 unf-2a switch connection terminal and a 5/16-24 unf-2a power connection terminal

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400