

View Online at <https://aerobasegroup.com/nsn/4320-01-444-3874>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Unthreaded external

**Current Type:**

Ac

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**End Application:**

Navy weapons code jk, wasp class lhd

**Maximum Discharge Flow Rate:**

40.0 gallons per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Features Provided:**

Self-priming

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Standard duty sealless pump for pumping some acids and other corrosives from 55gal drums; can be run dry without damage; motor has thermal overload protector and automatic reset; discharge has 0.75" hose connection; 1.5" diameter by 39" long polypropylene intake tube with polypropylene impeller; maximum pumping temperature 130 degrees f; includes 16ft 3-wire cord and plug and 6ft of vinyl discharge hose and clamps

**Frequency In Hertz:**

50.0 and 60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400