

View Online at <https://aerobasegroup.com/nsn/4320-01-444-3874>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Navy weapons code jk, wasp class lhd

Maximum Discharge Flow Rate:

40.0 gallons per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Features Provided:

Self-priming

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Standard duty sealless pump for pumping some acids and other corrosives from 55gal drums; can be run dry without damage; motor has thermal overload protector and automatic reset; discharge has 0.75" hose connection; 1.5" diameter by 39" long polypropylene intake tube with polypropylene impeller; maximum pumping temperature 130 degrees f; includes 16ft 3-wire cord and plug and 6ft of vinyl discharge hose and clamps

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400