

View Online at <https://aerobasegroup.com/nsn/4320-01-444-8717>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded external

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Sewage

**Pump Quantity:**

1

**Cooling Method:**

Blower cooled

**End Application:**

Navy weapons code th, strategic sealift conversion ships class

**Maximum Discharge Flow Rate:**

5.1 gallons per minute

**Total Head:**

80.000 feet

**Operating Speed At Rated Capacity:**

1725.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Lobular

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

15.0

**Discharge Connection Thread Size And Series/type Designator:**

1.250-11-1/2 npt

**Intake Connection Thread Size And Series/type Designator:**

4.000-8 npt

**Prime Mover Power Rating:**

1.0 horsepower

**Product Name:**

Transfer pump assembly

**Voltage In Volts:**

460.0

**Phase:**

Three

**Special Features:**

Rincluds grinder pump p/n 2600785-002, motor p/n 3600032-030, four 3/8-16 x 1in. Stainless steel cap screws p/n 2799946-067 and four 3/8in. Stainless steel lock washers p/n 2799944-010 for attaching pump body to motor

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400