

View Online at <https://aerobasegroup.com/nsn/4320-01-444-8717>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Sewage

Pump Quantity:

1

Cooling Method:

Blower cooled

End Application:

Navy weapons code th, strategic sealift conversion ships class

Maximum Discharge Flow Rate:

5.1 gallons per minute

Total Head:

80.000 feet

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Lobular

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

15.0

Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

4.000-8 npt

Prime Mover Power Rating:

1.0 horsepower

Product Name:

Transfer pump assembly

Voltage In Volts:

460.0

Phase:

Three

Special Features:

Rincluds grinder pump p/n 2600785-002, motor p/n 3600032-030, four 3/8-16 x 1in. Stainless steel cap screws p/n 2799946-067 and four 3/8in. Stainless steel lock washers p/n 2799944-010 for attaching pump body to motor

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400