

View Online at <https://aerobasegroup.com/nsn/4320-01-445-2181>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Unthreaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

End Application:

Navy weapons code th, strategic sealift conversion ships class

Maximum Discharge Flow Rate:

28.0 gallons per minute

Discharge Pressure:

150.0 pounds per square inch gage

Total Head:

50.000 feet

Suction Lift:

33.000 feet

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Voltage In Volts:

230.0

Phase:

Three

Special Features:

Water pump assembly

Frequency In Hertz:

50.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400