

View Online at <https://aerobasegroup.com/nsn/4320-01-445-9090>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Pump Quantity:

1

Cooling Method:

Blower cooled

End Application:

Weapons code 26f, aircraft f-16

Maximum Discharge Flow Rate:

2.0 gallons per minute

Discharge Pressure:

500.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3550.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.8

Discharge Connection Thread Size And Series/type Designator:

0.125-27 npt

Intake Connection Thread Size And Series/type Designator:

0.125-27 npt

Prime Mover Power Rating:

0.0769 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Magnet drive; carbon/polytetrafluoroethylene filled ryton gears; clockwise rotation; thermally protected motor; includes 68" power cord with line switch and nema 5-15 plug; six 0.3" diameter mounting holes in base

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400