

View Online at <https://aerobasegroup.com/nsn/4320-01-445-9090>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Pump Quantity:**

1

**Cooling Method:**

Blower cooled

**End Application:**

Weapons code 26f, aircraft f-16

**Maximum Discharge Flow Rate:**

2.0 gallons per minute

**Discharge Pressure:**

500.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

3550.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Gear

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

2.8

**Discharge Connection Thread Size And Series/type Designator:**

0.125-27 npt

**Intake Connection Thread Size And Series/type Designator:**

0.125-27 npt

**Prime Mover Power Rating:**

0.0769 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Magnet drive; carbon/polytetrafluoroethylene filled ryton gears; clockwise rotation; thermally protected motor; includes 68" power cord with line switch and nema 5-15 plug; six 0.3" diameter mounting holes in base

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400