

View Online at <https://aerobasegroup.com/nsn/4320-01-446-5952>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

12

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**End Application:**

Navy weapons code th, strategic sealift conversion ships class

**Maximum Discharge Flow Rate:**

40.0 gallons per minute

**Discharge Pressure:**

335.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

3450.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

12

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Current Rating In Amps:**

20.7 and 32.4 and 18.7 and 9.4

**Prime Mover Power Rating:**

10.00 horsepower

**Voltage In Volts:**

208.0 and 230.0 and 460.0

**Phase:**

Single/three

**Special Features:**

O-ring shaft seal with fixed seal driver; rotating and stationary rings are tungsten carbide; epdm secondary seal; nema pump; intake and discharge flanges are 2in. Ansi 250 lb. R.F., 8 bolt

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400