

View Online at <https://aerobasegroup.com/nsn/4320-01-446-5952>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

12

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Navy weapons code th, strategic sealift conversion ships class

Maximum Discharge Flow Rate:

40.0 gallons per minute

Discharge Pressure:

335.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

12

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

20.7 and 32.4 and 18.7 and 9.4

Prime Mover Power Rating:

10.00 horsepower

Voltage In Volts:

208.0 and 230.0 and 460.0

Phase:

Single/three

Special Features:

O-ring shaft seal with fixed seal driver; rotating and stationary rings are tungsten carbide; epdm secondary seal; nema pump; intake and discharge flanges are 2in. Ansi 250 lb. R.F., 8 bolt

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400