NSN 4320-01-447-2652

Centrifugal Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-447-2652

Intake Connection Type: Round flange Discharge Connection Quantity: 1 Drive Connection Type: Close coupled Media For Which Designed: Water, fresh End Application: Box controls; strategic sealift conversion ships class Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
Round flange Discharge Connection Quantity: 1 Drive Connection Type: Close coupled Media For Which Designed: Water, fresh End Application: Box controls; strategic sealift conversion ships class Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
Discharge Connection Quantity: 1 Drive Connection Type: Close coupled Media For Which Designed: Water, fresh End Application: Box controls; strategic sealift conversion ships class Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
Drive Connection Type: Close coupled Media For Which Designed: Water, fresh End Application: Box controls; strategic sealift conversion ships class Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
Drive Connection Type: Close coupled Media For Which Designed: Water, fresh End Application: Box controls; strategic sealift conversion ships class Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
Close coupled Media For Which Designed: Water, fresh End Application: Box controls; strategic sealift conversion ships class Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
Media For Which Designed: Water, fresh End Application: Box controls; strategic sealift conversion ships class Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
Water, fresh End Application: Box controls; strategic sealift conversion ships class Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
End Application: Box controls; strategic sealift conversion ships class Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
Box controls; strategic sealift conversion ships class Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
Maximum Discharge Flow Rate: 195.0 gallons per minute Total Head:
195.0 gallons per minute Total Head:
Total Head:
05 000 ()
85.000 feet
Operating Speed At Rated Capacity:
3580.0 revolutions per minute
Pump Rotation Direction:
Clockwise
Centrifugal Pump Design:
Axial flow
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A19400