## NSN 4320-01-447-3945

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-447-3945

Manual transfer Towns
Mounting Type:
Flange
Intake Connection Quantity:
1 Intelle Commention Towns
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Drive Connection Type:
Close coupled
End Application:
Weapon systems code ka, usns stalwart class tagos
Maximum Discharge Flow Rate:
13.8 gallons per minute and 9.2 gallons per minute
Discharge Pressure:
300.0 pounds per square inch gage
Operating Speed At Rated Capacity:
1800.0 revolutions per minute and 1200.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Pump Rotation Direction:
Counterclockwise
Rotary Pump Design:
Gear
Operation Method:
Powered
Drive Shaft Type:
D-type
Drive Shaft Length:
0.562 inches
Unpackaged Unit Length:
6.343 inches
Unpackaged Unit Width:
5.125 inches
Unpackaged Unit Height:
6.875 inches
Pump Basic Material:
Iron
Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

## NSN 4320-01-447-3945

Rotary Pump - Page 2 of 2



Intake Connection	Thread S	Size And	Series/type	Designator:
-------------------	----------	----------	-------------	-------------

1.000-11-1/2 npt

**Special Features:** 

Tang drive shaft; neoprene seal

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A19400