## NSN 4320-01-448-1323

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-448-1323

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Environmental Protection:
Dripproof
Pump Quantity:
1
Cooling Method:
Air to air cooled
End Application:
Weapon system code th, strageic sealift conversion class
Maximum Discharge Flow Rate:
35.0 gallons per minute
Total Head:
37.000 feet
Operating Speed At Rated Capacity:
3500.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Flactic mater

Electric motor

## NSN 4320-01-448-1323

Centrifugal Pump Unit - Page 2 of 2



nclosure Type:
Open
Current Rating In Amps:
0.94 and 0.47
Discharge Connection Thread Size And Series/type Designator:
1.250-11-1/2 npt
ntake Connection Thread Size And Series/type Designator:
1.500-11-1/2 npt
Prime Mover Power Rating:
0.5 horsepower
Voltage In Volts:
230.0 and 460.0
Phase:
Гhree
Special Features:
All bronze construction
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A19400