

View Online at <https://aerobasegroup.com/nsn/4320-01-448-2214>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Navy weapons code th, strategic sealift conversion ships class

Maximum Discharge Flow Rate:

1.5 gallons per minute and 3.0 gallons per minute

Discharge Pressure:

900.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1800.0 revolutions per minute and 3400.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Lobe

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.2

Discharge Connection Thread Size And Series/type Designator:

0.500-14 npt

Intake Connection Thread Size And Series/type Designator:

0.500-14 npt

Prime Mover Power Rating:

6.0 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Item includes gerotor pump, p/nb1.5-p-30a2, motor, adapter, coupling, two bearings and a shaft seal

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400