

View Online at <https://aerobasegroup.com/nsn/4320-01-448-6782>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

20.0 gallons per minute

Discharge Pressure:

125.0 pounds per square inch gage

Total Head:

11.000 feet

Operating Speed At Rated Capacity:

3250.0 revolutions per minute

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

0.72

Prime Mover Power Rating:

0.04 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Bronze casing; nonmetallic impeller; ceramic shaft; carbon bearing; maximum temperature 220deg f; all moving parts contained within a replaceable cartridge

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400