

View Online at <https://aerobasegroup.com/nsn/4320-01-448-7482>

Thread Direction:

Right-hand and right-hand

Torque Load Rating:

12500.0 inch-pounds

Mounting Type:

Face

Mounting Hole Diameter:

0.560 inches

Mounting Hole Quantity:

4

Thread Size:

1.312-12 and 1.312-12

Shaft Diameter:

1.000 inches

Mounting Bolt Circle Diameter:

4.243 inches

End Application:

Nimitz class cvn

Drive Shaft Type:

Woodruff keyway

Housing Material:

Nickel copper silicon alloy

Screw Thread Series Designator:

Un and un

Thread Location:

Internal and internal

Shaft Protrusion Length:

0.900 inches

Connection Quantity:

1 and 1

Connection Type:

Inlet and outlet

Maximum Working Pressure Rating At Specificationified Temperature Range:

900 psig at 50 degrees f to 200 degrees f

Connection Design:

Threaded and threaded

Sae Key Size Accommodated:

808

Constant Displacement Per Revolution:

5.500 cubic inches

Connection Government Specification/std:

Sae-16 both ends

Mounting Bolt Hole Spacing:

3.000 in. By 3.000 in.

Housing Surface Treatment:

Natural

Special Features:

U/o nu-torque inc p/n 44696 hydraulic actuator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T103-f