NSN 4320-01-448-7679

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-448-7679

| Prime Mover Quantity: |
|---|
| 1 |
| Prime Mover Cooling Medium: |
| Air |
| Stage Quantity: |
| 1 |
| Discharge Connection Quantity: |
| 1 |
| Current Type: |
| Dc |
| Media For Which Designed: |
| Water, fresh and water, salt |
| Environmental Protection: |
| Submersible |
| Pump Quantity: |
| 1 |
| Cooling Method: |
| Air to air cooled |
| End Application: |
| Zodiac hurricane 590 patrol boat |
| Maximum Discharge Flow Rate: |
| 13.33 gallons per minute |
| Pumping Element Operating Position: |
| Vertical |
| Centrifugal Pump Design: |
| Mixed flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Single |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Current Rating In Amps: |
| 2.8 |
| Prime Mover Power Rating: |
| 33.6 watts |
| Voltage In Volts: |
| 12.0 |
| Special Features: |
| Rule marine products model 20f bilge pump; has 36 mounting variations |

NSN 4320-01-448-7679

Centrifugal Pump Unit - Page 2 of 2



| | Life: |
|--|-------|
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400