

View Online at <https://aerobasegroup.com/nsn/4320-01-448-8683>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Environmental Protection:

Explosion proof

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Fluid reclamation system

Maximum Discharge Flow Rate:

10.4 gallons per minute

Discharge Pressure:

200.0 pounds per square inch gage

Total Head:

48.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

0.65 and 0.33 and 0.62 and 0.31

Discharge Connection Thread Size And Series/type Designator:

0.250-18 npt

Intake Connection Thread Size And Series/type Designator:

0.500-14 npt

Prime Mover Power Rating:

0.33 horsepower

Voltage In Volts:

220.0 and 440.0 and 230.0 and 460.0

Phase:

Three

Special Features:

Close coupled; 316 stainless steel

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400