

View Online at <https://aerobasegroup.com/nsn/4320-01-449-6642>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Navy weapons code jv, safeguard class ars

Maximum Discharge Flow Rate:

74.0 gallons per minute

Discharge Pressure:

75.0 pounds per square inch gage

Total Head:

70.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

5.6 and 5.4 and 2.7

Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Prime Mover Power Rating:

2.0 horsepower

Voltage In Volts:

208.0 and 230.0 and 460.0

Phase:

Three

Special Features:

Model npe close-coupled; liquid-end 304 s/s; standard seal; rotary carbon, stationary silicon carbide and viton elastomer; maximum temp. 250deg f

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400