

View Online at <https://aerobasegroup.com/nsn/4320-01-450-4711>

**Mounting Type:**

Flange

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Rigid coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils

**End Application:**

Navy weapons code ja, nimitz class cvn

**Maximum Discharge Flow Rate:**

7.0 gallons per minute

**Discharge Pressure:**

3000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

3600.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise

**Rotary Pump Design:**

Gear

**Operation Method:**

Powered

**Drive Shaft Type:**

Woodruff keyway

**Drive Shaft End Diameter:**

0.500 inches

**Drive Shaft Length:**

1.375 inches

**Discharge Connection Thread Size And Series/type Designator:**

0.500-14 nptf

**Intake Connection Thread Size And Series/type Designator:**

0.500-14 nptf

**Special Features:**

Cast iron two-stage, two-volume high/low hydraulic pump; has adjustable unloading valve factory preset at 650psi

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400