

View Online at <https://aerobasegroup.com/nsn/4320-01-450-6717>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Water, fresh and water, salt and oil

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Slipstream model omww0300 oil content monitor

Maximum Discharge Flow Rate:

8.0 gallons per minute

Discharge Pressure:

200.0 pounds per square inch gage

Operating Speed At Rated Capacity:

8000.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

3.0

Discharge Connection Thread Size And Series/type Designator:

0.250-18 npt

Intake Connection Thread Size And Series/type Designator:

O.375-18 npt

Prime Mover Power Rating:

75.0 watts

Voltage In Volts:

24.0

Special Features:

Emulsifier pump for right mounting panel assembly of oil content monitor

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400