

View Online at <https://aerobasegroup.com/nsn/4320-01-450-6717>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Dc

**Media For Which Designed:**

Water, fresh and water, salt and oil

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**End Application:**

Slipstream model omww0300 oil content monitor

**Maximum Discharge Flow Rate:**

8.0 gallons per minute

**Discharge Pressure:**

200.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

8000.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

3.0

**Discharge Connection Thread Size And Series/type Designator:**

0.250-18 npt

**Intake Connection Thread Size And Series/type Designator:**

O.375-18 npt

**Prime Mover Power Rating:**

75.0 watts

**Voltage In Volts:**

24.0

**Special Features:**

Emulsifier pump for right mounting panel assembly of oil content monitor

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400