

View Online at <https://aerobasegroup.com/nsn/4320-01-450-9748>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Liquid

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Navy w/s code jk, wasp class lhd

Maximum Discharge Flow Rate:

99.0 gallons per minute

Discharge Pressure:

29.0 pounds per square inch gage

Total Head:

67.000 feet

Suction Lift:

0.000 feet

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.94 and 1.47

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Prime Mover Power Rating:

1.5 horsepower

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Special Features:

Teel close coupled 1-1/2" bronze centrifugal pump model 1p793; type 416 stainless steel shaft

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400