

View Online at <https://aerobasegroup.com/nsn/4320-01-451-0099>

**Thread Direction:**

Right-hand

**Torque Load Rating:**

235.0 inch-pounds

**Key Length:**

1.7720 inches

**Mounting Type:**

Flange

**Key Width:**

0.3930 inches

**Mounting Hole Diameter:**

0.535 inches

**Mounting Hole Quantity:**

4

**Thread Size:**

0.875-14 and 0.875-14 and 0.4375-20

**Shaft Diameter:**

1.2605 inches

**Operating Speed At Rated Capacity In Rpm:**

246.0

**Mounting Bolt Circle Diameter:**

4.190 inches

**End Application:**

Navy weapons code jn, wasp class lhd

**Shaft Thread Size:**

0.3150-20.32

**Drive Shaft Type:**

Keyed and threaded

**Housing Material:**

Steel

**Screw Thread Series Designator:**

Unf

**Shaft Thread Direction:**

Right-hand

**Shaft Screw Thread Length:**

0.850 inches

**Shaft Rotation Direction:**

Clockwise and counterclockwise

**Accessory Components And Quantity:**

Magnetic speed pick-up with shroud connector 1

**Thread Location:**

Internal

**Shaft Protrusion Length:**

2.220 inches

**Connection Quantity:**

1 and 1 and 1

**Connection Type:**

Inlet and outlet and drain

**Maximum Working Pressure Rating At Specificationified Temperature Range:**

3000psi

**Connection Design:**

Threaded

**Key Height:**

0.3132 inches

**Displacement Type:**

Constant

**Constant Displacement Per Revolution:**

18.710 cubic inches

**Connection Government Specification/std:**

Sae j1926

**Special Features:**

M8 x 1.25-6h, 0.85in. Deep internal thread in end of output shaft; used in cement bin asy of pavement repair system

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T103-f