NSN 4320-01-451-0125

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-451-0125

| Thread Direction: |
|--|
| Right-hand |
| Torque Load Rating: |
| 7470.0 inch-pounds |
| Spline Minor Diameter: |
| 0.850 inches |
| Spline Major Diameter: |
| 0.998 inches |
| Mounting Type: |
| Flange |
| Spline Quantity: |
| 6 |
| Mounting Hole Diameter: |
| 0.535 inches |
| Mounting Hole Quantity: |
| 2 |
| Thread Size: |
| 0.875-14 and 0.875-4 and 0.4375-20 |
| Operating Speed At Rated Capacity In Rpm: |
| 153.0 |
| Mounting Bolt Circle Diameter: |
| 4.190 inches |
| End Application: |
| Weapons code djf, tractor, flightline towing |
| Shaft Thread Size: |
| 0.250-20 |
| Drive Shaft Type: |
| Splined, straight external and threaded |
| Housing Material: |
| Steel |
| Screw Thread Series Designator: |
| Unf |
| Shaft Thread Direction: |
| Right-hand |
| Shaft Screw Thread Length: |
| 0.600 inches |
| Shaft Rotation Direction: |
| Clockwise and counterclockwise |
| Thread Location: |
| Internal |
| Shaft Protrusion Length: |
| 1.130 inches |

NSN 4320-01-451-0125 Hydraulic Motor - Page 2 of 2



| Connection Quantity: |
|---|
| 1 and 1 and 1 |
| Connection Type: |
| nlet and outlet and drain |
| Maximum Working Pressure Rating At Specificationified Tempurature Range: |
| 1750psi |
| Connection Design: |
| Threaded |
| Spline Length: |
| 0.896 inches |
| Mounting Government Standard: |
| Sae a |
| Displacement Type: |
| Constant |
| Constant Displacement Per Revolution: |
| 18.710 cubic inches |
| Connection Government Specification/std: |
| Sae j1926 |
| Special Features: |
| Shaft spline per sae j499 6b; used in throat assembly of pavement repair system |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| Γ103-f |
| |