

View Online at <https://aerobasegroup.com/nsn/4320-01-451-0140>

Thread Direction:

Right-hand

Torque Load Rating:

3420.0 inch-pounds

Key Length:

1.250 inches

Mounting Type:

Flange

Key Width:

0.3125 inches

Mounting Hole Diameter:

0.535 inches

Mounting Hole Quantity:

4

Thread Size:

0.875-14 and 0.875-14 and 0.4375-20

Shaft Diameter:

1.250 inches

Operating Speed At Rated Capacity In Rpm:

576.0

Mounting Bolt Circle Diameter:

4.190 inches

End Application:

Weapons code djf, tractor, flightline towing

Drive Shaft Type:

Keyed

Housing Material:

Steel

Screw Thread Series Designator:

Unf

Shaft Rotation Direction:

Clockwise and counterclockwise

Accessory Components And Quantity:

Magnetic speed pickup with shroud connector 1

Thread Location:

Internal

Shaft Protrusion Length:

1.860 inches

Connection Quantity:

1 and 1 and 1

Connection Type:

Inlet and outlet and drain

Maximum Working Pressure Rating At Specificationified Tempurature Range:

3000psi

Connection Design:

Threaded

Key Height:

0.3125 inches

Displacement Type:

Constant

Constant Displacement Per Revolution:

7.970 cubic inches

Connection Government Specification/std:

Sae j1926

Special Features:

Shaft end thread 0.375-16 unc-2b; used for admix bin of pavement repair system

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T103-f